

UL 2651

PVC排线 PVC sheathed wire

■ 技术参数 Specifications

额定电压(Nominal voltage): 300V
额定温度(Temperature range): 105°C
标准(Standard): UL758

■ 应用 Applications

电子设备内部配线。
Internal wiring of electronic equipment.

导体: 镀锡铜
Conductor: Tinned copper

绝缘体: PVC
Insulation: PVC

备注: 可以做2-150并线
Note: Can perform 2-150 parallel wire stranding

■ 印字 Marking

E529032  AWM 2651 20AWG 105°C 300V VW-1 PVC  A/B 105°C 300V FT1 ZHONGWEI

■ 规格值 Product dimensions

线规 Size (AWG)	导体 Conductor		绝缘体 Insulation		完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)				
2*26	2*7/0.16	0.48	0.25		0.98*1.98	143	305/1000
2*24	2*7/0.20	0.61	0.25		1.11*2.24	89.3	305/1000
2*22	2*7/0.254	0.77	0.25		1.27*2.56	56.4	305/1000
2*20	2*21/0.18	0.92	0.25		1.42*2.86	35.2	305/1000
2*18	2*16/0.254	1.19	0.4		1.99*4.00	22.2	153/500
2*16	2*26/0.254	1.49	0.4		2.29*4.60	14	153/500
2*14	2*41/0.254	1.87	0.4		2.67*5.36	8.78	153/500

■ 颜色 Colours : All colours